



# RATINGS CHART – COMMERCIAL BASEBOARD

## MULTI/PAK 95



With or without dampers

Cover Type	Enclosure Height	Element Type	Tube Size & Material	Fin Size & Material	Fins Per Foot	Steam 1 PSI* Btu/Hr. Per Foot	HOT WATER RATINGS* BTU/HR./FT. (Flow Rate 3 Ft./Sec.)											
							110°F	120°F	130°F	140°F	150°F	160°F	170°F	180°F	190°F	200°F	210°F	220°F
95-10	9¾"	S-532	1¼" steel	4¼" steel	32	1254	251	326	414	501	564	665	765	865	978	1078	1191	1317
		S-540	1¼" steel	4¼" steel	40	1470	294	382	485	588	662	779	897	1014	1147	1264	1397	1544
		C-340	¾" copper	4¼" alum.	40	1680	336	437	555	672	756	891	1025	1159	1311	1445	1597	1764
		C-440	1" copper	4¼" alum.	40	1780	356	463	587	712	801	943	1086	1228	1388	1531	1691	1869
		C-540	1¼" copper	4¼" alum.	40	1745	349	454	576	698	785	925	1064	1204	1361	1501	1658	1832
95-17	16¾"	S-532	1¼" steel	4¼" steel	32	1351	270	351	446	540	608	716	824	932	1054	1162	1283	1419
		S-540	1¼" steel	4¼" steel	40	1577	315	410	520	631	710	836	962	1088	1230	1356	1498	1656
		C-340	¾" copper	4¼" alum.	40	1840	368	478	607	736	828	976	1123	1270	1436	1582	1748	1933
		C-440	1" copper	4¼" alum.	40	1950	390	507	644	780	878	1034	1190	1346	1521	1677	1853	2048
		C-540	1¼" copper	4¼" alum.	40	1911	382	497	630	764	860	1013	1166	1319	1491	1643	1815	2007
95-17 Two-tier element	16¾"	S-532	1¼" steel	4¼" steel	32	2153	431	560	710	861	969	1141	1313	1486	1679	1852	2045	2261
		S-540	1¼" steel	4¼" steel	40	2390	478	622	789	956	1076	1267	1458	1649	1864	2055	2271	2510
		C-340	¾" copper	4¼" alum.	40	2615	523	680	863	1046	1177	1386	1595	1804	2040	2249	2484	2746
		C-440	1" copper	4¼" alum.	40	2770	554	720	914	1108	1247	1468	1690	1911	2161	2382	2632	2909
		C-540	1¼" copper	4¼" alum.	40	2715	543	706	896	1086	1222	1439	1656	1873	2118	2335	2579	2851

\*Based on 65°F entering air temperature.