



RATINGS CHART – COMMERCIAL BASEBOARD

R-SERIES



Cover Type	Enclosure Height	Element Type	Tube Size and Material	Fin Size and Material	Fins Per Foot	Steam 1 PSI* Btu/Hr. Per Foot	HOT WATER RATINGS*											
							BTU/HR./FT. (Flow Rate 3 Ft./Sec.)											
							110°F	120°F	130°F	140°F	150°F	160°F	170°F	180°F	190°F	200°F	210°F	220°F
RL-10 RR-10	9 7/8"	S-532	1 1/4" steel	4 1/4" steel	32	1230	246	320	406	492	554	652	750	849	959	1058	1169	1292
		S-540	1 1/4" steel	4 1/4" steel	40	1330	266	346	439	532	599	705	811	918	1037	1144	1264	1397
		S-832	2" steel	4 1/4" steel	32	1270	254	330	419	508	572	673	755	876	991	1092	1207	1334
		C-340	3/4" copper	4 1/4" alum.	40	1647	329	428	544	659	742	872	1004	1136	1285	1417	1565	1730
		C-440	1" copper	4 1/4" alum.	40	1740	348	452	574	696	783	922	1061	1201	1357	1496	1653	1827
C-540	1 1/4" copper	4 1/4" alum.	40	1710	342	445	564	684	770	906	1043	1180	1334	1471	1625	1796		
RT-14 RR-14	14"	S-532	1 1/4" steel	4 1/4" steel	32	1280	256	333	422	512	576	678	781	883	998	1101	1216	1344
		S-540	1 1/4" steel	4 1/4" steel	40	1500	300	390	495	600	675	795	915	1035	1170	1290	1425	1575
		S-832	2" steel	4 1/4" steel	32	1320	264	343	436	528	594	700	805	911	1030	1135	1254	1386
		C-340	3/4" copper	4 1/4" alum.	40	1714	343	446	566	685	771	908	1046	1183	1337	1474	1628	1800
		C-440	1" copper	4 1/4" alum.	40	1820	364	473	601	728	819	965	1110	1256	1420	1565	1729	1911
C-540	1 1/4" copper	4 1/4" alum.	40	1780	356	463	587	712	801	943	1086	1228	1388	1531	1691	1869		
RT-21 RR-21	21"	S-532	1 1/4" steel	4 1/4" steel	32	1380	276	359	455	552	621	731	842	952	1076	1187	1311	1449
		S-540	1 1/4" steel	4 1/4" steel	40	1610	322	419	531	644	725	853	982	1111	1256	1385	1530	1691
		S-832	2" steel	4 1/4" steel	32	1460	292	380	482	584	657	774	891	1007	1139	1256	1387	1533
		C-340	3/4" copper	4 1/4" alum.	40	1878	376	488	620	751	846	996	1146	1296	1465	1615	1784	1972
		C-440	1" copper	4 1/4" alum.	40	1990	398	518	657	796	896	1055	1214	1373	1552	1711	1891	2090
C-540	1 1/4" copper	4 1/4" alum.	40	1950	390	507	644	780	878	1034	1190	1346	1521	1677	1853	2048		
RT-21 RR-21 Two-tier element	21"	S-532	1 1/4" steel	4 1/4" steel	32	2200	440	572	726	880	990	1166	1342	1518	1716	1892	2090	2310
		S-540	1 1/4" steel	4 1/4" steel	40	2440	488	634	805	976	1098	1293	1488	1684	1903	2098	2318	2562
		S-832	2" steel	4 1/4" steel	32	2230	446	580	736	892	1004	1182	1360	1539	1739	1918	2119	2342
		C-340	3/4" copper	4 1/4" alum.	40	2668	534	694	881	1067	1201	1414	1627	1840	2081	2294	2535	2801
		C-440	1" copper	4 1/4" alum.	40	2830	566	736	934	1132	1274	1500	1726	1953	2207	2434	2689	2972
C-540	1 1/4" copper	4 1/4" alum.	40	2770	554	720	914	1108	1247	1468	1690	1911	2161	2382	2632	2909		
RT-28 RR-28	28"	S-532	1 1/4" steel	4 1/4" steel	32	1400	280	364	462	560	630	742	854	956	1092	1204	1330	1470
		S-540	1 1/4" steel	4 1/4" steel	40	1680	336	437	554	672	756	890	1025	1159	1310	1445	1596	1764
		S-832	2" steel	4 1/4" steel	32	1480	296	385	488	592	666	784	903	1021	1154	1273	1406	1554
		C-340	3/4" copper	4 1/4" alum.	40	1907	381	496	629	763	858	1010	1163	1315	1487	1640	1811	2002
		C-440	1" copper	4 1/4" alum.	40	2020	404	525	667	808	909	1071	1232	1394	1576	1737	1919	2121
C-540	1 1/4" copper	4 1/4" alum.	40	1980	396	515	653	792	891	1049	1208	1366	1544	1703	1881	2079		
RT-28 RR-28 Two-tier element	28"	S-532	1 1/4" steel	4 1/4" steel	32	2260	452	588	746	904	1017	1198	1379	1559	1763	1944	2147	2373
		S-540	1 1/4" steel	4 1/4" steel	40	2460	492	640	812	984	1107	1304	1501	1697	1919	2116	2337	2583
		S-832	2" steel	4 1/4" steel	32	2270	454	590	749	908	1022	1203	1385	1566	1771	1952	2157	2384
		C-340	3/4" copper	4 1/4" alum.	40	2860	572	744	944	1144	1288	1516	1745	1973	2231	2460	2718	3004
		C-440	1" copper	4 1/4" alum.	40	3030	606	788	1000	1212	1364	1606	1848	2091	2363	2606	2879	3182
C-540	1 1/4" copper	4 1/4" alum.	40	2970	594	772	980	1188	1337	1574	1812	2049	2317	2554	2822	3119		
RT-28 RR-28 Three-tier element	28"	S-532	1 1/4" steel	4 1/4" steel	32	2580	516	671	851	1032	1161	1367	1574	1780	2012	2219	2451	2709
		S-540	1 1/4" steel	4 1/4" steel	40	2800	560	728	924	1120	1260	1484	1708	1932	2184	2408	2660	2940
		S-832	2" steel	4 1/4" steel	32	2660	532	692	878	1064	1197	1410	1623	1835	2075	2288	2527	2793
		C-340	3/4" copper	4 1/4" alum.	40	3390	678	881	1119	1356	1525	1797	2068	2339	2644	2915	3220	3559
		C-440	1" copper	4 1/4" alum.	40	3590	718	934	1185	1436	1616	1903	2190	2477	2800	3087	3411	3770
C-540	1 1/4" copper	4 1/4" alum.	40	3520	704	915	1162	1408	1584	1866	2147	2429	2746	3027	3344	3696		

*Based on 65°F entering air temperature.

SLANT/FIN CORPORATION, Greenvale, NY 11548 • Phone: (516) 484-2600
 FAX: (516) 484-5921 • In Canada: Slant/Fin LTD/LTEE, Mississauga, Ontario
 www.slantfin.com

©Slant/Fin Corp. 2007